



STANDARD TOLERANCES		
T1	+0.000 -0.001	+0.00 -0.02
W1	+0.000 -0.001	+0.00 -0.02
A	+0.020 -0.000	+5 -0
L	+0.020 -0.000	+5 -0
	INCH	METRIC

Series	R	MT*	MW
MiniLifter	.250	.31	.24
UniLifter	.406	.49	.49
XL Series	.875	1.00	1.00
Metric	10mm	15mm	10mm

*Note: MT may increase for strength.

NOTE:
Altering the MT & MW dimensions (Minimum Thickness and Width of heel area) is not recommended.

CORE BLADES

Dimension	Tolerance
T1	<input type="checkbox"/> Standard + -
T2	REF
D1	+ -
D2	+ -
W1	<input type="checkbox"/> Standard + -
W2	REF
C1	+ -
C2	+ -
A	<input type="checkbox"/> Standard + -
L	<input type="checkbox"/> Standard + -
Quantity:	

Series:

- | | |
|---|--|
| <input type="checkbox"/> MiniLifter
U-Coupling = UCM50 | <input type="checkbox"/> UniLifter
U-Coupling = UCU87 |
| <input type="checkbox"/> XL Series
U-Coupling = UCX175 | <input type="checkbox"/> Metric
U-Coupling = UCMM22 |

Material:

- | | |
|--|---|
| <input type="checkbox"/> H-13
Hardness = 38-42 Rc | <input type="checkbox"/> Other:
Material _____ |
| <input type="checkbox"/> Ampco
Hardness = 30 Rc | Core Hardness _____ |
| | Surface Hardness _____ |
| | Treatment _____ |

FAX TO 800-462-6653 OR E-MAIL TECH@PROCOMPS.COM

CONTACT:	COMPANY NAME:	PHONE #:	FAX #:
REFERENCE #:	ACCOUNT #:	E-MAIL ADDRESS:	