



STANDARD TOLERANCES		
T	+0.00 -.001	+0.00 -.02
W	+0.00 -.001	+0.00 -.02
L	+0.06 -.00	+2.0 -0.0
	INCH	METRIC

Series	R	MT*	MW
MiniLifter	.250	.31	.24
UniLifter	.406	.49	.49
XL Series	.875	1.00	1.00
Metric	10mm	15mm	10mm

*Note: MT may increase for strength.
 NOTE:
 Altering the MT & MW dimensions (Minimum Thickness and Width of heel area) is not recommended.

Series:

- MiniLifter U-Coupling = UCM50
- UniLifter U-Coupling = UCU87
- XL Series U-Coupling = UCX175
- Metric U-Coupling = UCMM22

Material:

- H-13 Hardness = 38-42 Rc
- Ampco Hardness = 30 Rc
- Other: _____
- Material _____
- Core Hardness _____
- Surface Hardness _____
- Treatment _____

CORE BLADE #1			
Dimension	Tolerance		
T	<input type="checkbox"/> Standard	+	-
W	<input type="checkbox"/> Standard	+	-
L	<input type="checkbox"/> Standard	+	-
Quantity:			

CORE BLADE #2			
Dimension	Tolerance		
T	<input type="checkbox"/> Standard	+	-
W	<input type="checkbox"/> Standard	+	-
L	<input type="checkbox"/> Standard	+	-
Quantity:			

CORE BLADE #3			
Dimension	Tolerance		
T	<input type="checkbox"/> Standard	+	-
W	<input type="checkbox"/> Standard	+	-
L	<input type="checkbox"/> Standard	+	-
Quantity:			

CORE BLADE #4			
Dimension	Tolerance		
T	<input type="checkbox"/> Standard	+	-
W	<input type="checkbox"/> Standard	+	-
L	<input type="checkbox"/> Standard	+	-
Quantity:			

FAX TO 800-462-6653 OR E-MAIL TECH@PROCOMPS.COM

CONTACT:	COMPANY NAME:	PHONE #:	FAX #:
REFERENCE #:	ACCOUNT #:	E-MAIL ADDRESS:	